



PS701

PS7 Series Position Sensor

Features

- Operated by suitable Magnet
- Repeatability of operation
- Shunt or direct magnet operation
- Multiple Mode of Operation
- Totally encapsulated

Comments

- Pocan Material Housing
- Normally Open
- Surface Mounted by single fixing hole
- Low Profile Package 3.7mm

Applications

- Door Interlocks
- Hook Switches
- Security Systems
- Safety Interlocks
- Position Indication

PS 701

PS7 Series | Position Sensor

Material

Housing Material	Pocan
Contact Material	Ruthenium
Operating Temperature °C	-30 to 85
Housing Colour	Black

Mechanical Specifications

Shock	50g for 11ms duration
Vibration	35g up to 500Hz
IP	IP65

Switching

Switch Action (Reed Switch)	SPST
Max Switching Voltage VDC	160
Max Switching Voltage VAC	110
Max Switching Current Amps	0.25
Max Switching Load Watt	5
Operate Mode	Direct Axis, Parallel Axis
Contact Form	A

Cable

Cable Length	2 x 0.5M
Connection Type	Stripped Cables
Cable Type	7/0.2mm PVC insulated
Cable Colour	Black/Black

Mounting

Fitment	Surface
Mounting	Any Axis

Technical Drawing

