



PS801

PS8 Series

Position Sensor

Features

- Adjustable operated PM8 Magnet
- Repeatability of operation
- Shunt or direct magnet operation
- Multiple Mode of Operation
- Totally encapsulated

Comments

- Threaded Barrel Mounted
- Normally Open
- Stainless Steel Material Housing
- Overall length 65mm Threaded Area
- fitted with 2 lock nuts

Applications

- Door Interlocks
- Hook Switches
- Security Systems
- Safety Interlocks
- Position Indication

PS 801

PS8 Series | Position Sensor

Material

Housing Material	Stainless Steel
Contact Material	Ruthenium
Operating Temperature °C	-30 to 120
Housing Colour	Stainless Steel

Mechanical Specifications

Shock	50g for 11ms duration
Vibration	35g up to 500Hz
IP	IP67

Switching

Switch Action (Reed Switch)	PST
Max Switching Voltage VDC	200
Max Switching Voltage VAC	250
Max Switching Current Amps	1
Max Switching Load Watt	40
Operate Mode	Direct Axis, Parallel Axis
Contact Form	A

Cable

Cable Length	2 x 0.5M
Connection Type	Stripped Cable
Cable Type	16/0.2mm PVC Double insulated
Cable Colour	Grey outer Blue/Brown inner

Mounting

Thread	M10 x 1.5
Mounting	Any Axis

Technical Drawing

