



VCS Series • Top or Bottom • Level Sensor

Features

- Overall length less than 60mm
- Internal Fit
- 22mm diameter float
- Polypropylene Material

Comments

- High or Low level sensing
- N/O or N/C by float reversal
- Reed Switch Reliability (UL File E153493)
- Encapsulated Magnet
- Interface Option Available

Applications

- Water high or low Level
- Condensate level alarm
- Chemical high or low level
- Cooling systems
- Coolant level indication

VCS-03 VCS Series • Top or Bottom • Level Sensor

Material		Cable	
Housing Material Float Material	Polypropylene Polypropylene	Cable Length Connection Type	2 x 0.1M Stripped Cables
Contact Material	Ruthenium	Cable Type	22 AWG 16/0.2mm PVC insulated
Float SG Operating Temperature °C Medium Housing Colour Float Colour	0.54 -30 to 70 Water Black White	Cable Colour	Black/Black
Mechanical Specifications		Mounting	
	3 half-sine pulses of 11mS		

Shock	3 half-sine pulses of 11mS, 30G	Thread	1/8
Vibration Float Diameter IP	35g up to 500Hz 22.3mm IP65	Fitment Mounting	Internal Fit Top or Bottom entry

Technical Drawing

Switching	
Switch Action (Reed Switch)	
Max Switching Voltage VDC	
Max Switching Voltage VAC	
Max Switching Current Amps	
Max Switching Load Watt	
Operate Mode	
Contact Form	

250 1 30 N/C with float at bottom stop A

SPST 200

